



**Kompis Utleie.no**

**Tlf 475 01 504**

UTLEIE AV MASKINER OG VERKTØY  
TIL MARKEDETS BESTE PRISER

## Specifications

MODELS	GR-12		GR-15		GR-20	
MEASUREMENTS	Metric	US	Metric	US	Metric	US
Working Height	5.48 m	17 ft 5 in	6.47 m	20 ft 8 in	8.07 m	25 ft 11 in
Platform Height	3.48 m	11 ft 5 in	4.47 m	14 ft 8 in	6.07 m	19 ft 11 in
A Height (stowed)	1.57 m	5 ft 2 in	1.57 m	5 ft 2 in	1.98 m	6 ft 6 in
B Length (stowed)	1.35 m	4 ft 5 in	1.35 m	4 ft 5 in	1.35 m	4 ft 5 in
C Width 75 cm	2 ft 5.5 in	75 cm	2 ft 5.5 in	80 cm	2 ft 7.5 in	
D E Platform Dimensions (l x w)						
Standard platform	88 x 75 cm	35 x 29.5 in	88 x 75 cm	35 x 29.5 in	88 x 75 cm	35 x 29.5 in
Standard platform with extension	1.4 m x 75 cm	55 x 29.5 in	1.4 m x 75 cm	55 x 29.5 in	1.4 m x 75 cm	55 x 29.5 in
Stock Picker platform	88 x 73 cm	35 x 28.8 in	88 x 73 cm	35 x 28.8 in	88 x 73 cm	35 x 28.8 in
Stock Picker platform with adjustable tray	1.4 m x 73 cm	56 x 28.8 in	1.4 m x 73 cm	56 x 28.8 in	1.4 m x 73 cm	56 x 28.8 in
Standard AWP platform	69 x 51 cm	27 x 26 in	69 x 51 cm	27 x 26 in	69 x 51 cm	27 x 26 in
Narrow AWP platform	66 x 51 cm	26 x 20 in	66 x 51 cm	26 x 20 in	66 x 51 cm	26 x 20 in
Standard fibreglass platform	74 x 67 cm	29 x 26.5 in	74 x 67 cm	29 x 26.5 in	74 x 67 cm	29 x 26.5 in
Narrow fibreglass platform	66 x 56 cm	26 x 22 in	66 x 56 cm	26 x 22 in	66 x 56 cm	26 x 22 in

PRODUCTIVITY						
Lift Capacity	227 kg	500 lbs	227 kg	500 lbs	159 kg	350 lbs
Ground Clearance	6.35 cm	2.5 in	6.35 cm	2.5 in	6.35 cm	2.5 in
Drive Speed (stowed)	4.0 km/h	2.5 mph	4.0 km/h	2.5 mph	4.0 km/h	2.5 mph
Drive Speed (raised)	0.8 km/h	0.5 mph	0.8 km/h	0.5 mph	0.8 km/h	0.5 mph
Gradeability*	30%	30%	30%	30%	30%	30%
Turning Radius-inside	Zero	Zero	Zero	Zero	Zero	Zero
Controls	12 V proportional controls		12 V proportional controls		12 V proportional controls	
Tyres	Non-marking tyres		Non-marking tyres		Non-marking tyres	

POWER						
Power Source	4 batteries, 6 V 225 Ah batteries		4 batteries, 6 V 225 Ah batteries		4 batteries, 6 V 225 Ah batteries	
Hydraulic System Capacity	8.33 L	2.2 gal	8.33 L	2.2 gal	8.33 L	2.2 gal

WEIGHT						
Weight**	717 kg	1,581 lbs	994 kg	2,192 lbs	1,111 kg	2,451 lbs

WEIGHT						
CE Compliance option						
Fully certified load sensor (EN280)						
AS 1418.10						

\*Gradeability applies to driving on slopes. See operators manual for details regarding slope rating.

\*\*Weight will vary depending on options and/or country standards.

# Features

## STANDARD FEATURES

### MEASUREMENTS

#### GR-12

- 5.48 m (17 ft 5 in) working height
- 3.48 m (11 ft 5 in) platform height
- 1.57 m (5 ft 2 in) stowed height
- 1.35 m (4 ft 5 in) stowed length
- 75 cm (2ft 5.5 in) width

#### GR-15

- 6.47 m (20 ft 8 in) working height
- 4.47 m (14 ft 8 in) platform height
- 1.57 m (5 ft 2 in) stowed height
- 1.35 m (4 ft 5 in) stowed length
- 75 cm (2ft 5.5 in) width

#### GR-20

- 8.07 m (25 ft 11 in) working height
- 6.07 m (19 ft 11 in) platform height
- 1.98 m (6 ft 6 in) stowed height
- 1.35 m (4 ft 5 in) stowed length
- 80 cm (2ft 7.5 in) width

### PRODUCTIVITY

- High strength aluminium rigid mast system
- Narrow 75 cm to 80 cm width and 1.35 m length
- Low 38 cm entry height
- On-board diagnostics and battery indicator
- Proportional drive and lift controls
- Maximum manoeuvrability steering system
- Alarm system and flashing beacon



## OPTIONS & ACCESSORIES

### PRODUCTIVITY

- Stock picker platform with adjustable tray
- Extension platform
- Maintenance-free battery
- Automotive horn
- Fluorescent tube caddy

### POWER

- Power wheel assist with dual battery package
- Dual battery package

## Genie Australia

591 Boundary Road, Darra, Qld 4076  
PO Box 394, Richlands, Qld 4077  
Tel: + 61 7 3375 1660  
Toll Free In Australia: 1800 331 660  
Fax: + 61 7 3375 1002

## European Offices

### UK

The Maltings  
Wharf Road  
Grantham NG31 6BH  
UK  
Tel: +44 (0)1476 584333  
Fax: +44 (0)1476 584334

### France

10, ZA de la Croix St. Mathieu  
28320 Gallardon  
France  
Tel: +33 (0)2 37 26 09 99  
Fax: +33 (0)2 37 26 09 98

### Germany

Finienweg 3  
28832 Achim/Bremen  
Germany  
Tel: +49 (0)4202 8852-0  
Fax: +49 (0)4202 8852-25

### Spain

Gai 'a 31, Pol. Ind. Pl 'a d'en Coll  
08110 Montcada i Reixac  
Barcelona  
Spain  
Tel: +34 93 572 50 90  
Fax: +34 93 572 50 91

### Scandinavia

Tagenevägen 72  
425 37 Hisings Kärra  
Sweden  
Tel: +46 31 57 51 00  
Fax: +46 31 57 90 20

## Genie United States

18340 NE 76th Street  
P.O. Box 97030  
Redmond, Washington 98073-9730  
USA  
Tel: +1 425 881-1800  
Fax: +1 425 883-3475

**WEB:** [www.genieindustries.com.au](http://www.genieindustries.com.au)

## Distributed By: